Application No.: 10/581,521 Attorney Docket No.: 26222A

## IN THE CLAIMS

(Currently Amended) A process Process for manufacturing a moulded molded composite part comprising; in which the moulded part is obtained by moulding providing at least one composite sandwich material including at least one manufactured core adhered to at least one composite skin;

molding said at least one composite sandwich material into a molded composite part in a mold with the application of heat and pressure, the

wherein said sandwich material has incorporated therein at least one incorporating an expansion agent that reacts during said molding step to press said composite skin against a wall of said mold moulding.

- (Currently Amended) The process Process according to claim 1, wherein characterized in that the expansion agent is incorporated into the core of the sandwich material.
- (Currently Amended) The process Process-according to claim 1, wherein
   eharacterized in that the expansion agent is applied to incorporated into at least one member selected from the core and the and/or its skin.

## 4.-6. Canceled

- (Currently Amended) The process Process-according to claim 1-Claim 6, further
  comprising the step of incorporating the expansion agent within the core.
- (Currently Amended) The process Process-according to claim 1-Claim 6, further
  comprising the step of incorporating the expansion agent between the core and the composite
  skin.

Application No.: 10/581,521 Attorney Docket No.: 26222A

(Currently Amended) The process Process of according to claim 1 Claim 6, further
comprising the step of reacting the expansion agent by heating the expansion agent in the
mold-mould.

- (Currently Amended) The process Process of according to claim 1-Claim 6, wherein
  the expansion agent is selected from the group consisting of water, azodicarbonamide,
  sulphonyl hydrazide[[,]] and sodium bicarbonate/citric acid mixtures.
- 11. (Currently Amended) The process <u>Process of according to claim 1-Claim 6</u>, wherein the expansion agent represents from 0.5 to 5% by weight of the core.
- (Currently Amended) The process Process of according to claim 1-Claim 6, wherein
  the thickness of the composite skin is less than 10% of the thickness of the composite
  sandwich material.